

ABENE VHF-550 CNC

STANDARDEQUIPMENT

- Complete coolant system
- Hydraulic Tool Clamping
- CE-protection mounted on table
- Machine lamp 24V Halogen
- Automatic central lubrication system
- Keys and manuals
- Spare parts book and accuracy report
- Automatic gearbox with frequency controlled spindle.
- Heidenhain TNC-410/426/i530



Boring spindle (Option)

ABENE VHF-550 The machine is built according to the unique ABENE "angular frame plane" design concept, which has the spindle head sideways mounted. This radical (World Exclusive) feature allows rapid and precisely uniform changing from Vertical to Horizontal machining. The ergonomically environment, along with the benefits of different Heidenhain controls, allows the **ABENE VHF-550 CNC** to let you decide how best to turn your idea into a presentable product with maximum economy and efficiency.

TECHNICAL DATA	VHF-550	VHF-550 /BS	UNIT
TABLE			
Table surface	1200 x 450	1200 x 450	mm
T-slot	6 x 18 H7	6 x 18 H7	mm
Max Load	400	400	kg
MOVEMENT			
Longitudinal	650	650	mm
Cross	480	480	mm
Vertical	475	475	mm
Feeds n:o	Stepless	Stepless	
Rapid feed X,Y	6000	6000	mm/min
Rapid feed Z	4000	4000	mm/min
Feed motor AC (Z)	4,0 (10,5)	4,0 (10,5)	Nm
SPINDLE			
Spindle speed	55-4000	55-4000	rpm
Spindle	ISO40 / DIN2079	ISO40 / DIN2079	
Spindle speeds n:o	Freq. Control	Freq. Control	Stepless
Spindle Power	7,5	7,5	kW
Spindle head swivel	0-140	0-140	Degree
Spindle quill	--	75	mm
Hand wheel	--	3 (option)	mm/rev.
Weight	2300	2300	kg
Net Weight	2100	2100	kg



ABENE Machine AB

Box 147, 615 23 Valdemarsvik, SWEDEN

Tel: +46 123 51175

Fax: +46 123 51567

E-mail: sales@abene.se

www.abene.se